
**METHOD AND APPARATUS FOR RESETTING PROGRAMMING
PARAMETERS WITHIN AN IMPLANTABLE MEDICAL DEVICE**

5

Field of the Invention

10 The present invention generally relates to implantable medical devices and to external programmer devices used in connection therewith and in particular to methods and apparatus for programming implantable medical devices using the external programmer device.

Background of the Invention

15 A wide range of implantable medical devices are provided for surgical implantation into humans or animals. Common examples include the cardiac pacemaker and the implantable cardioverter defibrillator (ICD). Other examples include devices for stimulating or sensing portions of the brain, spinal cord, muscles, bones, nerves, glands or other body organs
20 or tissues.

Implantable medical devices, particularly pacemakers and ICDs, are often configured to be used in conjunction with an external programmer device which allows a physician to program the operation of the device to, for example, control the specific parameters by which the
25 pacemaker detects arrhythmia conditions and responds thereto. For instance, the external programmer may allow the physician to specify the sensitivity with which the pacemaker or ICD senses electrical signals within the heart and to further specify the amount of electrical energy to be employed in administering therapy. Additionally, the external
30 programmer may be configured to receive and display a wide variety of diagnostic information detected by the implantable device, such as electrical heart signals sensed by the device.

Current state of the art implantable medical devices may have dozens or hundreds of parameters that can be individually programmed

using the external programmer. The programmable parameters permit the operation of the medical device to be tailored to the needs of the particular patient to provide optimal therapy while minimizing the risk of unnecessary therapy. However, the process of initially programming the many parameters can be a fairly laborious one even when a state of the art external programmer is used. In this regard, to program the many parameters, the physician may need to select numerous individual data entry screens using the external programmer and then manually enter specific parameters using a key pad. To minimize the amount of parameters that need to be manually entered, the external programmer may provide default values for many of the parameters. Nevertheless, for many patients, numerous parameters need to be individually manually entered by the physician. After the parameters have been entered, the external programmer generates programming commands for transmission to the implanted device via a telemetry system. U.S. Patent Number 5,431,691 to Snell et al. entitled "Method and a System for Recording and Displaying a Sequential Series of Pacing Events" provides a detailed description of the operation of one exemplary pacemaker and external programmer system and is incorporated by reference herein.

Thus, a laborious initial programming procedure often needs to be performed by the physician for each patient receiving an implantable medical device. Unfortunately, in some cases, the parameters need to be subsequently modified. For example, the patient may complain of shortness of breath or other medical problems requiring the physician to repeat some or all of the programming steps to modify the programming parameters. In some cases, the updated programming does not benefit the patient. Accordingly, the physician may need to yet again perform many of the programming procedures to reset the programming to values that had been previously entered. For some patients, over a period of months or years, the programming parameters may need to be frequently modified, then modified again, often returning the programming state of the implantable device to a previous programming state.

Accordingly, it would be desirable to provide an external programmer capable of automatically resetting the programming parameters of an implantable medical device to a previously programmed set of parameters such that the device can be easily reset to a previous programming state without re-entry of the programming parameters. Aspects of the present invention are directed to that end.

To facilitate the selection of a previous programming state, it would be desirable to provide the external programmer with the capability to display the differences between two or more programming states or to permit a physician to select a previous programming state and then modify only selected parameters from that state to create a new programming state. It would also be desirable to provide the external programmer device with the capability to merge the parameters from two or more previous programming states to create a new modified programming state. Additionally, some state of the art external programmer devices provide modeling software which models the performance of the implantable medical device based on a particular set of programming parameters and generates graphical displays permitting the physician to easily gauge the expected performance of the device. Thus, it would also be desirable to provide such an external programmer with the capability to display models of the behavior of the implantable medical device based upon two or more selected previous programming states to facilitate selection of the programming state providing the best performance. Other aspects of the invention are directed to these various features.

Summary of the Invention

The present invention generally relates to implantable medical devices and to external programmer devices used in connection therewith and in particular to methods and apparatus for programming implantable medical devices using the external programmer device.

In accordance with a first aspect of the invention, a device is provided for resetting the programming state of an implantable medical device. The device includes means for maintaining parameters representative of a plurality of programming states including a current programming state and at least one other programming state. Means are also provided for receiving a reset signal for resetting the programming state of the implantable device to a selected one of the other programming states and for resetting the programming of the implantable device to the selected state.

In an exemplary embodiment, the programming parameters for the plurality of programming states are maintained within the implantable medical device. To reset the programming state, the external programmer controls the implanted device to transmit the programming parameters for the plurality of states to the external programmer for storage therein, and then displays information representative of the programming states to a physician operating the external programmer to permit selection of one of the states. After a state has been selected, the external programmer transmits a pointer or other signal identifying the selected state to the implantable device and, in response thereto, the implantable device reprograms its internal functional components in accordance with the selected programming state.

Also in the exemplary embodiment, means are provided to permit the physician to modify any or all of the parameters of the selected state prior to resetting the programming of the implantable medical device. If any of the programming parameters are changed, the external programmer device generates appropriate programming commands for transmission to the implantable device to reflect the updated parameters.

In accordance with a second aspect of the invention, a device is provided for use with an external programmer of an implantable medical device for displaying differences between two or more programming states of the medical device. The device includes means for maintaining parameters representative of a plurality of programming states and means

for generating a display indicating the differences, if any, between the selected states. In this manner, a physician operating the external programmer device can easily identify differences between the parameters corresponding to different states to facilitate selection of a particular one of the states.

In accordance with a third aspect of the invention, a device is provided for use with an external programmer of an implantable medical device for merging parameters from two or more programming states to create a new programming state. The device includes means for maintaining parameters representative of a plurality of programming states and means for receiving a merge signal for resetting the programming state to a combination of selected states of the plurality of programming states. Means are also provided for resetting the programming of the implantable device to the combination of the first selected states. In accordance with a fourth aspect of the invention, a device is provided for use with an external programmer of an implantable medical device wherein the external programmer is capable of modeling the behavior of the implantable device based upon sets of programming parameters and is capable of displaying graphs representative of the models.

The device includes means for maintaining parameters representative of a plurality of programming states and means for receiving a compare signal initiating a comparison of device behavior models for selected programming states of the plurality of programming states. The device additionally includes means for generating models for the behavior of the implantable device for the selected programming states based upon the parameters of the selected states and for displaying graphs representative of models generated for the selected states. In this manner, a physician operating the external programmer can easily compare the behavior models for two or more programming states to identify the state which will provide the best performance for the patient. Thereafter, the programming of the implantable medical device

can be easily reset to the programming state providing the best expected behavior.

Preferably, the external programmer device is configured to implement all of these aspects of the invention. Method embodiments of the invention are also achieved. Other advantages of the invention are provided as well.

Brief Description of the Drawings

FIG. 1 shows an implantable pacemaker coupled to a heart via a pair of electrical leads.

FIG. 2 is a perspective view of an external programmer that may be used for communicating with the implantable pacemaker of **FIG. 1**.

FIG. 3 is a flow chart illustrating steps performed by both the external programmer and implantable device of **FIGS. 1 and 2** for use in resetting a programming state of the implantable device to a previously programmed state.

FIG. 4 is a block diagram illustrating a memory unit used in coordination with the implantable medical device for use in storing a set of programming states to permit a current programming state of the device to be reset to another state using the method of **FIG. 3**.

FIG. 5 is a exemplary display screen presented by the external programmer of **FIG. 2** displaying a set of previous programming states and sets of functions to be performed using the previous programming states in accordance with the method of **FIG. 3**.

FIG. 6 is a flow chart illustrating steps performed by the external programmer and implantable device of **FIGS. 1 and 2** for use in resetting the programming state of the implantable device to another programming state while also permitting selected parameters to be updated prior to reprogramming.

FIG. 7 is a flow chart of steps performed by the external programmer and implantable device of **FIGS. 1 and 2** for use in permitting

the programming parameters of two or more states to be merged together to create a new programming state.

FIG. 8 is a flow chart illustrating method steps performed by the external programmer and implantable device of **FIGS. 1 and 2** for use in permitting a comparison of the differences between two or more selected programming states to be displayed on the external programmer.

FIG. 9 is a flow chart illustrating steps performed by the external programmer and implantable device of **FIGS. 1 and 2** for use in displaying a comparison of models of the behavior of two or more selected programming states using the external programmer.

FIG. 10 is block diagram of the primary components of the external programmer of **FIG. 2**.

FIG. 11 is block diagram of the primary components of the implantable pacemaker of **FIG. 1**.

Detailed Description of the Invention

The invention relates to improved techniques for programming implantable medical devices. The invention will be described primarily with reference to a pacemaker used in conjunction with an external programmer device, but principles of the invention are applicable to other implantable medical devices such as ICDs and to other external control devices as well.

FIG. 1 illustrates an exemplary implantable pacemaker **10** coupled to a heart **12** by way of a ventricular lead **14** and an atrial lead **16**. Ventricular lead **14** includes an electrode **18** positioned in the right ventricle **20** of the heart and atrial lead **16** includes an electrode **22** positioned in the right atrium **24** of the heart. Various internal components of the pacemaker **10** operate to sense the electrical activity of the heart, such as the presence of P-waves and R-waves, using electrodes **18** and **22** and to selectively stimulate the heart in response to events sensed within the heart by conducting electrical stimulation pulses to the heart

using the electrodes. The pacemaker **10** may be configured to operate in either a single-chamber mode or a dual-chamber mode.

The operation components of pacemaker **10** of **FIG. 1** is programmed by programming signals received from an external programmer (**FIG. 2**). **Table I** provides a list of exemplary programming parameters employed by the external programmer to program the operation of the pacemaker **10**.

PROGRAMMING PARAMETER	PROGRAMMED FUNCTION
Mode	Pacemaker Mode Programmed
Base Rate	Heart Base Rate Programmed
Rest Rate	Heart Rest Rate Programmed
Maximum Tracking Rate	Maximum Pacemaker Tracking Rate Programmed
Maximum Sensor Rate	Maximum Pacemaker Sensor Rate Programmed
Rate Responsive AV/PV Delay	Rate Responsive AV/PV Delay Programmed

TABLE I

10

Programming parameters received from the external programmer **100** are stored within the pacemaker **10**. More specifically, parameters corresponding to a particular programming session are stored together, along with any default parameters, within the pacemaker **10** as a unique programming state. Whenever a new programming session is initiated to modify or otherwise update the programming parameters, the modified parameters, along with previously programmed or default parameters, are stored within the pacemaker **10** as a new programming state. Accordingly, after a number of programming sessions, the pacemaker **10** stores a number of programming states corresponding to the number of programming sessions. The pacemaker **10** also stores a pointer identifying which of the programming states is the current programming

state. Typically, the pointer indicates that the most recent programming state is the current state. As will be described in greater detail below, the external programmer **100** is configured to cause the pacemaker **10** to reset the current programming state to one of the previous programming states, i.e., the external programmer **100** can transmit signals causing the pointer identifying the current state to be reset, i.e., altered, to one of the other states. In response thereto, pacemaker **10** reprograms the operation of its internal components in accordance with the parameters of the programming state identified by the new pointer.

FIG. 2 illustrates an exemplary external programmer **100** configured for programming pacemaker **10** (**FIG. 1**) and for displaying information received from the pacemaker **10** such as diagnostic information. External programmer **100** includes a printer **102** for printing out a graphical representation of the information received from the pacemaker **10** and a display screen **104** for providing a graphical representation of the information such as, for example, an intracardiac electrogram (IEGM). The programming of the pacemaker **10** and the generation of graphic displays of information received from the pacemaker **10** is subject to the control of a physician or other user operating the external programmer **100**. To this end, external programmer **100** presents various menus on display screen **104** for use in controlling operation of the external programmer **100** to program pacemaker **10** (**FIG. 1**) using any of the parameters listed above in **TABLE I**. Various menus are also presented on display screen **104** for use in controlling operation of the external programmer **100** to generate displays on display screen **104** of parameters used to the pacemaker **10**. External programmer **100** preferably receives menu selections from the physician through a touch screen **109** which overlays display screen **104**. The actual programming of the pacemaker **10** is achieved using telemetry head **106** which includes telemetry circuitry **107** coupled to a telemetry wand **108** (see **FIG. 10**) which, in use, is placed in proximity to the pacemaker **10**. While it is presently preferred that the telemetry circuitry

107 be remotely coupled, e.g., via a cable, to the telemetry wand **108**, the distribution of the associated circuitry of the telemetry head **106** between the telemetry circuitry **107** and the telemetry wand **108** is not significant to the application of the present invention.

5 As noted, the external programmer **100** is also configured to permit a physician operating the external programmer **100** to reset a current programming state of the pacemaker **10** to a previous programming state. The external programmer **100** also provides a set of related functions applicable to the various programming states. More specifically, the
10 external programmer **100** may provide one or more of the following additional functions: (1) after the pacemaker **10** has been reset to a previous programming state, the external programmer **100** can reset the pacemaker **10** to one of the programming states originally programmed subsequent to the newly reset state; (2) the external programmer **100**
15 permits the pacemaker **10** to be set to a new programming state based upon a previous programming state wherein one or more programming parameters are modified; (3) the external programmer **100** permits the pacemaker **10** to be set to a new programming state based upon a combination of two other programming states; (4) the external
20 programmer **100** permits a physician using the external programmer **100** to display differences between selected programming states; and (5) the external programmer **100** permits the physician operating the external programmer **100** to display graphical models of the expected behavior of two or more programming states.

25 With reference to **FIGS. 3 and 6-9**, the methods employed by the external programmer **100** and pacemaker **10** to provide the aforementioned functionality will now be described. **FIG. 3** illustrates exemplary steps performed by the external programmer **100** and pacemaker **10** of **FIGS. 1 and 2** for use in resetting the programming
30 state of the pacemaker **10** to a previous state or, if the external programmer state has already been reset to a previous state, to reset the pacemaker **10** to one of the subsequently programmed states. Initially, at

step **200**, the physician operating the external programmer **100** selects a reset command from a menu presented by the external programmer **100**. In response to the reset command, the external programmer **100** sends a command to the pacemaker **10** through the telemetry head **106** for
5 controlling the pacemaker **10** to transmit the parameters for all of the programming states stored within the pacemaker **10** to the external programmer **100**. In response thereto, the pacemaker **10** transfers the parameters for all states at step **202** and the parameters are stored within the external programmer **100** at step **204**. In the alternative, parameters
10 can be automatically transferred whenever a communication session between the external programmer **100** and the pacemaker **10** is initiated, for example, to transfer the programming parameters along with other operational parameters such as the model and serial number of the implanted device and any historical information pertaining to the patient
15 stored within the device.

In any case, the pacemaker **10**, at step **202**, also transfers a pointer identifying the current programming state of the pacemaker **10** for storage along with the programming states in step **204**. In many cases, the pointer will merely identify the most recent programming state of the
20 pacemaker **10**. However, if the programming state has previously been reset by the external programmer **100**, then the pointer will identify one of the earlier programming states as the most current state.

FIG. 4 illustrates an exemplary memory unit **220** of the pacemaker **10** employed to store the various programming states. Preferably, the
25 memory unit **220** is contained within a parameter storage unit **120** within the pacemaker **10**. Alternatively, the memory storage unit **220** can be contained within a portion of a parameter storage unit **133** within the external programmer **100** (see **FIG. 10**). For each programming state, the memory unit stores all of the parameters **222** for that state including
30 parameters that were specifically entered as well as any default parameters. Additionally, the memory unit **220** stores the date and time **224** that the pacemaker **10** was programmed to the corresponding state.

The memory unit **220** also stores a pointer **226** identifying the current programming state of the pacemaker **10**. Note that any two programming states may differ from one another by only a single parameter or by many parameters. In some cases, every parameter of a particular state will
5 differ from all of the parameters of the other programming states.

Referring again to **FIG. 3**, at step **206**, the external programmer **100** displays the programming parameters of all of the programming states **222** transmitted from the pacemaker **10** along within the identification of the current state. **FIG. 5** illustrates an exemplary display
10 screen presented by the external programmer **100** listing the various programming states. As can be seen, an arrow identifies the current programming state. In the example of **FIG. 5**, all of the parameters corresponding to each state are not concurrently displayed. However, if desired, a physician operating the external programmer **100** may select a
15 function entitled "DISPLAY DETAILS" (not shown) to cause the external programmer **100** to display all of the parameters corresponding to the selected state.

Continuing with **FIG. 3**, at step **208**, the external programmer **100** receives a pacemaker **10** state selection from the physician. In the
20 example of **FIG. 5**, the physician may select, for example, the state identified as state "#5". Depending upon the particular programming of the external programmer **100**, this may be accomplished by using arrow keys on the keyboard **110** of the external programmer **100** to scroll through the list of states until a desired state is highlighted, and then
25 pressing "enter". Once the state has been selected by the physician, the external programmer **100**, at step **210**, generates and transmits a command to the pacemaker **10** to reset the programming state to the selected state. The command includes a pointer identifying the selected state. In response thereto, the pacemaker **10**, at step **212**, reads the
30 parameters corresponding to the selected state from its memory unit. Then, at step **214**, the pacemaker **10** reprograms its internal components based upon those parameters. Finally, at step **216**, the pacemaker **10**

updates the pointer **226** stored in the memory unit **220** to identify the selected state.

Thus, the physician operating the external programmer **100** easily and conveniently resets the programming of the pacemaker **10** to a different programming state by merely selecting the state and entering the appropriate reset commands. Hence, with only a few keystrokes, the physician may reset dozens of parameters of the pacemaker without the need to individually enter any of the parameters and without risk of inadvertent programming errors that could otherwise occur if the physician were required to enter all programming parameters.

Finally, at step **218**, the pacemaker **10** sends an acknowledgment signal back to the external programming acknowledging that the programming state of the pacemaker **10** had been reset to the selected state and, in response thereto, the external programmer **100** displays the acknowledgment on the display screen **104** for viewing by the physician.

In some circumstances, the physician may wish to reset the programming state of the pacemaker **10** to a previous state while changing some or all of the programming parameters. **FIG. 6** illustrates steps performed by the external programmer **100** and pacemaker **10** for implementing this function. Many of the steps of **FIG. 6** are similar to those of **FIG. 3**. Accordingly, only pertinent differences will be described in detail.

After the reset function is selected in step **300**, the parameters for all of the states and the pointer **226** identifying the current state are transferred from the pacemaker **10** to the external programmer **100** using steps **302** and **304**. The external programmer **100** then displays all states along with an identification of the current state (e.g., as seen in **FIG. 5**). If the states have already been transferred to the external programmer **100**, perhaps during the processing of a previous reset command, then it is not necessary to repeat the transfer. The physician then selects a "RESET WITH MODIFICATIONS" function at step **308** and selects a state. At step **310**, the external programmer **100** reads all parameters for the selected

state and presents a list of the parameters on the display screen (not separately shown). At step **312**, the physician enters updates to any of the parameters. Depending upon the programming of the external programmer **100**, this may be achieved by scrolling through the parameters using the arrow button of the keyboard **110** until a selected parameter is highlighted, then manually typing in new numerical values for the selected parameter. In other implementations, the physician may select from a list of preprogrammed acceptable values for each programming parameter.

Once any or all of the parameters of the selected state have been updated, the external programmer **100** generates, at step **314**, commands for reprogramming the modified parameters within the pacemaker **10**. These commands may be the same type of commands used to initially program the pacemaker **10**. At step **316**, the commands are transmitted to the pacemaker **10** which, at step **318**, responds by programming its internal components based upon the commands. At step **320**, the pacemaker **10** stores all of the parameters corresponding to the selected state, as modified, as a new state. At step **322**, the pointer identifying the current state is updated to identify the new state.

Thus, unlike the embodiment of **FIG. 3** wherein the pacemaker **10** merely updates its internal pointer **226** to identify the selected state, in the embodiment of **FIG. 6**, a new state is stored and the pointer is set to identify the new state. Depending upon the particular implementation, when transmitting parameters to the pacemaker **10** at step **316**, the external programmer **100** may either selectively transmit programming commands corresponding to only those parameters that were modified or may transmit programming commands corresponding to all programmable parameters associated with the selected state. If all parameters are not transmitted, then the pacemaker **10**, when creating the new programming state, reads all unmodified parameters corresponding to the selected state from the memory unit and copies those parameters into the new

state. As can be appreciated, a wide variety of particular implementations may be provided consistent with the general principles of the invention.

Thus, **FIG. 6** provides a method for creating a new state based upon a previous state while updating some or all of the programming parameters. The method of **FIG. 6** is particularly helpful whenever the physician wishes to set the pacemaker **10** to a new state which is very similar to a previous state but differs only with respect to a few parameters.

In other circumstances, the physician may wish to set the pacemaker **10** to a new programming state which is a combination of two previous programming states. For example, the physician may wish to set the pacemaker **10** to a state which combines all of the non-default parameters of one state and all of the non-default parameters of another state. To this end, the physician selects the "MERGE" function from the display screen of **FIG. 5** in step 400 and, in response thereto, the pacemaker **10** and external programmer **100** perform steps **402** through **406** to transfer parameters corresponding to all states from the pacemaker **10** to the external programmer **100** and to display the states using the external programmer **100**. As before, if the states have already been transferred to the external programmer **100**, it may not be necessary to repeat the transfer. At step **408**, the physician selects two or more states to be merged together to create a new state. At step **410**, the external programmer **100** reads the parameters corresponding to all of the selected states and merges the parameters together.

In the preferred implementation, merging is performed as follows. The external programmer **100** first identifies all parameters which are exactly the same in both programming states and copies those parameters into the new state. Then, the external programmer **100** identifies any parameters which differ from the corresponding parameter of the other state to determine whether the parameter in one of the two states is a default parameter and, if so, the external programmer **100** uses the non-default parameter as the new parameter for the new state. Thus,

non-default parameters take precedence over default parameters. In the event the parameters for the two states are both non-default parameters, then the external programmer **100** selects the parameter having the more recent update time. Thus, more recently programmed parameters take
5 precedence over earlier programmed parameters. In other implementations, different priority rules may be employed.

At step **412**, the external programmer **100** accepts updates, if any, from the physician to the parameters of the merged state. Once updates have been entered, the external programmer **100** then generates
10 programming commands for programming the pacemaker **10** to the new merged state at step **416** and transmits the commands to the pacemaker **10** at step **418**. The pacemaker **10** receives the commands, reprograms its internal components based upon the parameters provided therein, saves the parameters as a new state, and updates the pointer **226** to
15 identify the new state using steps **420** through **424**.

Thus, **FIG. 7** illustrates a method for creating a new state by merging two previous states. Merging is particularly useful when the physician wishes to reprogram the pacemaker **10** to a combination of previous states without needing to re-enter a potentially large number of
20 parameters.

In some circumstances, the physician may merely wish to view the differences between two states and, if so, the physician selects, at step **500**, the "DIFFERENCES" function from the display of **FIG. 5**. In response thereto, the external programmer **100** and pacemaker **10**
25 perform the steps of **FIG. 8**. As before, parameters corresponding to all states and a pointer identifying the current state are transmitted (if not already stored in the external programmer **100**) from the pacemaker **10** to the external programmer **100** and displayed thereon using steps **502** through **506**. At step **508**, the external programmer **100** receives a
30 selection of two or more states for comparison and reads the parameters corresponding to the two selected states. At step **510**, the external programmer **100** examines the parameters to identify any differences and

displays an indication of those differences on a display screen (not shown). Depending upon the particular programming of the external programmer **100**, the external programmer **100** may display only those parameters which differ or may display all parameters while highlighting those which differ. The method of **FIG. 8** is particularly useful to display differences between two states prior to selecting which states are to be merged together.

If the external programmer **100** is provided with software for modeling the behavior of the pacemaker **10** based upon a set of programming parameters, then it may be desirable for the physician to display a comparison of the behavior models for two different programming states using the external programmer **100**. If so, the physician selects, at step **600**, the "COMPARE MODELS" function from the display screen of **FIG. 5** and, in response thereto, the steps illustrated in **FIG. 9** are performed by the pacemaker **10** and the external programmer **100**. As before, the pacemaker **10** transfers parameters corresponding to all programming states to the external programmer **100** for storage and display thereon using steps **602-606**. At step **608**, the physician selects two or more states for model behavior comparison. At step **610**, the external programmer **100** reads the parameters corresponding to the selected states and, at step **612**, generates models of the expected behavior of the pacemaker **10** for each of the selected states.

At step **614**, the external programmer **100** graphically displays the behavior models for the selected states to permit the physician to quickly and easily evaluate differences in the expected behavior. The compare models function thus enables a physician to quickly compare the expected behavior for two or more programming states and can be used, for example, to help the physician identify one particular state for use in resetting the pacemaker **10** or for identifying two or more states for merging.

FIGS. 10 and 11 are block diagrams illustrating the primary components of the pacemaker **10** and external programmer **100** of **FIGS. 1 and 2** for use in performing the various methods described above in **FIGS. 3 and 6-9**. More specifically, **FIG. 10** illustrates pertinent components of the external programmer **100** and **FIG. 11** illustrates pertinent components of the pacemaker **10**. The components shown in **FIGS. 10 and 11** will be briefly described.

Referring first to **FIG. 10**, a controller **110** of external programmer **100** controls the graphic display device **104** to display the aforementioned menus from which the physician may select, among other options, to initially program the pacemaker **10**, to reset programming parameters to an earlier programming state or to perform any of the other programming state functions described above.

The physician initially programs the pacemaker **10** following its implantation by using a programming unit **112** which controls the graphic display device **104** to display a list of the programming options corresponding to, for example, the programming options listed in **TABLE I**. The physician selects one or more of the programming options from the list then enters any pertinent parameters such as the applicable pacing mode, rate values or delay values from one or more display screens (not separately shown) presented by the programming unit **112** using the graphic device **104**. A transmitter unit **114** of telemetry head **106** transmits appropriate command signals to the pacemaker **10** to program the pacemaker **10** in accordance with the selected options. The physician may also enter patient data such as the name of the patient, any medications prescribed to the patient, any diagnoses of conditions of the patient, and the identification of any electrical leads or other accessory devices used in connection with the pacemaker **10**. This information is entered via the display screens of the external programmer **100** and then transferred to the pacemaker **10** along with the programming commands.

Referring to **FIG. 11**, the programming commands transmitted by the external programmer **100** are received by a receiver unit **116**. A

controller **118** operates in response to the received commands to program appropriate pacemaker functional units **119** to operate in accordance with the programming parameters using an internal programming unit **117**.

Additionally, the programming parameters are forwarded by the receiver
5 unit **116** to a parameter storage unit **120** which stores information pertaining to the received programming parameters as an initial programming state. The parameter storage unit **120** may be configured in part as the memory storage unit **220** as shown in **FIG. 4**. The pacemaker
10 **10** may be configured to employ default parameters in case any specific parameters are not transmitted to the pacemaker **10**. In such a case, the default parameters are also stored as part of the programming state in the storage unit **120** under the control of the controller **118**.

If one or more programming parameters are subsequently reprogrammed, then the parameters corresponding to the modified
15 programming state are also stored within the parameter storage unit **120** as a new state. The programming parameters for the previous state are retained as well. Pointer **226**, as shown in **FIG. 4**, is set to identify the new state as the current state. After several reprogramming sessions, several programming states are stored in storage unit **120**. A circular
20 buffer may be employed for the parameter storage unit **120** for storing programming states such that the earliest states may be ultimately overwritten.

Eventually, the physician may need to reset the programming state to a previous programming state or to perform one of the other
25 aforementioned programming state functions. To reset the programming parameters, the physician selects RESET using a menu, such as that shown in **FIG. 5**. Controller **110** of the external programmer **100** of **FIG. 10** forwards appropriate retrieval commands to the pacemaker **10** (**FIG. 4**) via the transmitter unit **114** of the telemetry head **106**. The
30 retrieval commands are received by the receiver unit **116** of the pacemaker **10** of **FIG. 11** and forwarded to the parameter storage unit **120** which, in turn, retrieves all stored programming parameters for all states

along with the pointer to the current state for transmission to the external programmer **100** via a transmitter unit **130**. The various programming state parameters and the pointer are received by a receiver unit **132** of the telemetry head **106** of the external programmer **100** of **FIG. 10**, stored
5 in a parameter storage unit **133** and also forwarded to a programming state controller unit **134**.

Programming state controller unit **134** operates to perform the reset function, as described in detail above, using a reset unit **135**. To this end, the reset unit **135** generates a display such as the one shown in
10 **FIG. 5** listing all of the programming states along with the pointer identifying the current state and accepts user input identifying the state to which the pacemaker **10** is to be reset. In response thereto, the reset unit **135** sets the pointer to the selected state and forwards the pointer to transmitter unit **114** for transmission to the pacemaker **10**. Receiver unit
15 **116** of the pacemaker **10** (**FIG. 11**) receives the pointer and forwards the pointer to a state processing unit **136** which accesses parameter storage unit **120** to read out the parameters corresponding to the state identified by the transmitted pointer. The state processing unit then forwards the parameters to internal programming unit **117** for reprogramming functional
20 units **119** of the pacemaker **10**. Once the functional units **119** have been reprogrammed, a confirmation signal is sent under the control of the state processing unit **136** to the external programmer **100** for display thereon.

Referring again to **FIG. 10**, programming state controller unit **134** additionally includes a reset with modifications unit **136**, a merge unit **137**,
25 a display differences unit **138** and a display model comparison unit **139** which operate to perform the functions described above in **FIGS. 6-9**, respectively. As these functions have already been described in detail, they will not be further described herein, other than to note that the display model comparison module employs a model generation unit **140**
30 to generate models of the behavior of the pacemaker **10** based upon the parameters of selected programming states.

Alternative configurations of the present invention should be apparent to one of ordinary skill in the art. For example, in a preferred embodiment, the current state pointer is modified to select the current operating configuration. In an alternative configuration, the order of the operating configurations in the parameter storage unit **120** could be used to define the current operating configuration. For example, the first location (or other predefined location) could be the current operating configuration. Accordingly, the current operating configuration could be reset, i.e., modified, by changing the order of the operating configurations in the parameter storage unit **120**. This function could be accomplished by the external programmer **100** reordering (according to the selected operating configuration) the data received from the parameter storage unit **120** and then generating a reset signal that transferred the newly ordered parameter data back to the parameter storage unit **120** in the implantable medical device **10**. Accordingly, the current operating configuration of the implantable medical device **10** would be reset.

In the presently preferred embodiment, a plurality of operating configurations are stored within the memory storage unit portion **220** of the parameter storage unit **120** of the pacemaker **10**. This enables the use of a different external programmers since the previously used operating configurations would be stored in the implantable medical device **10**. In an alternative embodiment, the operating configurations could instead be stored within the memory storage unit portion **220** of the parameter storage unit **133** of the external programmer, e.g., in a semiconductor memory device or on a hard disk.

What has been described are systems for resetting the programming of a pacemaker. The various functional components of the exemplary system may be implemented using any appropriate technology including, for example, microprocessors running software programs or application specific integrated circuits (ASICs) executing hard-wired logic operations. Although described with respect to pacemakers and ICDs used in conjunction with an external programmer, aspects of the invention

are applicable to other systems, such as systems employing other implantable medical devices or systems employing other types of external interfaces for use with the implantable device. The exemplary embodiments of the invention described herein are merely illustrative of the invention and should not be construed as limiting the scope of the invention. For example, while an exemplary use with a two-lead implantable pacemaker has been shown, one of ordinary skill in the art would readily appreciate the applicability of the present invention to an implantable cardiac stimulation device that used more than two leads, e.g., an implantable cardioverter defibrillator (ICD) or a pacemaker that stimulated/monitored more than two chambers (for example all four chambers) of the heart individually. Consequently, the present invention is defined by the appended claims.